







# SR-X series

	Model	Frequency Range	Sensitivity (1W/1m)	Nominal Coverage	Power Handling*	Max SPL**	Nominal Impedance	Dimensions (HxWxD)***	Weight
	SR4702X	60Hz to 18kHz	95 dB	85°x 85°	600 W	129 dB	8 ohms	648 x 403 x 356 mm 25.5 x 15.9 x 14 in	29 kg 64 lbs
	SR4722X	42Hz to 18kHz	95 dB	85°x 85°	600 W	129 dB	8 ohms	686 x 486 x 333 mm 27 x 19.1 x 13.1 in	27.2 kg 60 lbs
	SR4725X	35Hz to 18kHz	98 dB	90°x 40°	600 W	132 dB	8 ohms	718 x 616 x 435 mm 28.3 x 24.3 x 17.1 in	37.2 kg 82 lbs
	SR4726X	35Hz to 20kHz	97 dB	90°x 50°	600 W	131 dB	8 ohms	883 x 616 x 435 mm 34.8 x 24.3 x 17.1 in	48.5 kg 107 lbs
	SR4731X	39Hz to 20kHz	98 dB	90°x 50°	1200 W	135 dB	4 ohms	1067 x 616 x 435 mm 42 x 24.3 x 17.1 in	59.9 kg 132 lbs
	SR4732X	39Hz to 21kHz	98 dB	90°x 50°	1200 W	135 dB	4 ohms	1067 x 616 x 435 mm 42 x 24.3 x 17.1 in	62.1 kg 137 lbs

\* IEC filtered noise with 6 dB crest factor






\*\* Calculated based on peak power handling and sensitivity

\*\*\* Height does not include 11.2 mm (0.45 in) clearance for rubber feet



JBL Professional  
8500 Balboa Blvd.  
Northridge, CA 91329  
Tel: (818) 894-8850  
www.jblpro.com

# SR-X series

	Model	Frequency Range	Sensitivity (1W/1m)	Nominal Coverage	Power Handling*	Max SPL**	Nominal Impedance	Dimensions (HxWxD)***	Weight
	SR4733X	37Hz to 20kHz	100 dB	90°x 50°	1200 W	137 dB	4 ohms	1219 x 616 x 435 mm 48 x 24.3 x 17.1 in	65.8 kg 145 lbs
	SR4735X	36Hz to 20kHz	97 dB	70°x 50°	600 W	131 dB	8 ohms	946 x 616 x 479 mm 37.3 x 24.3 x 18.9 in	50.8 kg 112 lbs
	SR4715X	35Hz to 300Hz	100 dB	N/A	1200 W	137 dB	4 ohms	1067 x 584 x 653 mm 42 x 23 x 25.7 in	53.5 kg 118 lbs
	SR4718X	38Hz to 300Hz	98 dB	N/A	600 W	132 dB	4 ohms	616 x 613 x 610 mm 24.3 x 24.1 x 24.0 in	39.9 kg 88 lbs
	SR4719X	30Hz to 300Hz	101 dB	N/A	1200 W	138 dB	4 ohms	765 x 1219 x 616 mm 30.1 x 48 x 24.3 in	85.3 kg 188 lbs

\* IEC filtered noise with 6 dB crest factor

\*\* Calculated based on peak power handling and sensitivity

\*\*\* Height does not include 11.2 mm (0.45 in) clearance for rubber feet



JBL Professional  
8500 Balboa Blvd.  
Northridge, CA 91329  
Tel: (818) 894-8850  
www.jblpro.com